



1500*300mm 66W

Features and Advantages

- Ultra slim and minimalistic panel design
- TUV CE/SAA external constant current driver adopted
- Epistar SMD LED Chip
- Slim white-anodised Aluminium border for classic minimalist style
- Soft and uniform lighting for comfortable viewing environment
- Life span of 80,000h with low light decay
- High stability and reliability
- 5-year Warranty



DIMENSIONS



ITEM	A	B	C
LED RECTANGULAR PANEL	1496mm	296mm	12mm

SPECIFICATIONS

Physical Specifications

Size (mm)	1500*300
Materials	AL Frame + PMMA diffuser
IP Class	IP20
Installation	Recessed
Net Weight	3900g
Work Environment	Indoor

Electrical Specifications

Input Voltage	85V-265V AC
Frequency Range	50/60Hz
Power Factor	>0.9
Power	66W
Certification	CE, RoHS
Protection Function	Over-current protection, Surge Protection
Operation Temperature	-25°C ~ 50°C
Lifespan	80.000 hours

Optical Specifications

Luminous Efficiency (lm/w)	>80
Color Temperature (CCT)	4000K
Lumen Flux	6230 LM
Color Rendering Index	≥80
Beam Angle	120° - 180°

1500*300mm 66W

PHOTOMETRIC DATA

